

Bluetooth

Commandes

Interrogation/Configuration

rfkill

Activation/désactivation des périphériques sans fil

```
rfkill list
```

hcitool

Configuration connexion bluetooth

```
hcitool dev
```

hciconfig

Configuration périphériques Bluetooth

```
hciconfig
```

[Haut de page](#)

Dépannage

Problème bluetooth

L'interface bluetooth reste down :

```
hciconfig
hci0:  Type: Primary  Bus: USB
      BD Address: 00:00:00:00:00:00  ACL MTU: 0:0  SCO MTU: 0:0
      DOWN
      RX bytes:0  acl:0  sco:0  events:0  errors:0
```

```
TX bytes:3 acl:0 sco:0 commands:1 errors:0
```

Pas de controleur par défaut

```
[root@localhost]~ > bluetoothctl show
No default controller available
[root@localhost]~ > bluetoothctl devices
No default controller available
```

Vérifications

```
systemctl status bluetooth
lsusb -v | grep Bluetooth | grep DeviceProtocol
lsusb -t | grep Wireless
hciconfig up
bluetoothctl show
bluetoothctl devices
```

[How to debug bluetooth problems](#)

[Haut de page](#)

From:

<https://wiki.iot-acs.fr/> - **Wiki**

Permanent link:

<https://wiki.iot-acs.fr/doku.php?id=all:bibles:linux:bluetooth>

Last update: **2024/06/14 11:10**

